

Zinplast Sp. z o.o. ul.Garbarska 41 32-340 Wolbrom POLAND

The above organisation is hereby entitled, on the basis of certificate No. 19 07 90310 001 and the appendant test reports, to affix the certification body's certification mark shown below to the following product (see description below).



Pipes made from polyethylene for atternative installation techniques

- = Test of resistance to slow
- crack growth

 Point loading last
 Penalrellon lest
- State book-scand double

Requirement:

The product fulfils the requirements of PAS 1075 for all alternative installation methods. Restriction: when applying the pipe bursting method to grey cast-iron pipes, the maximum operating pressure must be limited to max. 5 bar in SDR 11 pipes and max. 3.2 bar in SDR 17 pipes. The product also fulfils the stricter requirements outlined in MUC-KSP-A 3026.

Product description:

ZINPLAST Solid RC Gaz/W and SW

One-layer solid-wall pipes made of polyethylene PE 100-RC, fully colored or with colored stripes for the following conditions of use and nominal diameters:

- Pipes made of polyethylene for alternative installation methods as per PAS 1075 (Type 1)
- Nominal diameters: 20 to 63 mm, SDR 11 and SDR 17
- For gas-, water- and sewage-water applications

Production site: Zinplast Sp. z o.o. ul.Garbarska 41 32-340 Wolbrom POLAND

This certificate is valid to July 2022. Factory surveillance is carried out annually.

Munich, 19 July 2019

TÜV SÜD Industrie Service GmbH Institute for Plastics

i. A. Schweize

TÜV SUD Industrie Service GmbH is a testing, certification and inspection body approved by Deutsches Institut für Bautechnik (DIBt), Berlin



Zinplast Sp. z o.o. ul.Garbarska 41 32-340 Wolbrom **POLAND**

The above organization is hereby entitled, on the basis of certificate No. 19 07 90310 002 and the appendant test reports, to affix the certification body's certification mark shown below to the following product (see description below).



Pipes made from polyethylene for atternative installation techniques

- = Test of resistance to slow
- crack growth

 Point loading less
 Penetration lest

www.torowood.coids

Requirement:

The product fulfils the requirements of PAS 1075 for all alternative installation methods. Restriction: when applying the pipe bursting method to grey cast-iron pipes, the maximum operating pressure must be limited to max. 5 bar in SDR 11 pipes and max. 3.2 bar in SDR 17 pipes. The product also fulfils the stricter requirements outlined in MUC-KSP-A 3026.

Product description:

ZINPLAST Solid 2RC Gaz/W and SW

Coextruded pressure pipes made of polyethylene PE 100-RC, with colored stripes or fully color-coded for the following applications and nominal diameters:

- Pipes made from polyethylene for alternative installation techniques as per PAS 1075 (Type 2)
- Nominal diameters: 75 to 500 mm, SDR 11 and SDR 17
- For gas-, water- and sewage-water applications

Production site:

Zinplast Sp. z o.o. ul.Garbarska 41 32-340 Wolbrom **POLAND**



This certificate is valid to July 2022. Factory surveillance is carried out annually.

Munich, 19 July 2019

TÜV SÜD Industrie Service GmbH Institute for Plastics



i. A. Schweize

TUV SOD beautiful Service GmbH is a testing, certification and inspection body approved by Deutsches Institut für Bautechnik (DIBt), Berlin